

Pillar caps and copings

How to cover your walls in elegance

Weser pillar caps and copings are essential parts of your surrounding walls. They protect your pillars and walls elegantly from damp, and thus help to keep them in good condition for a long time. The width of the coping depends on the width of the wall, including rendering. All pillar caps and copings are throated.



CHR1 - single weathered coping



CHR0 - flat coping



CHR2 - twice weathered copings



CP0 - flat pillar cap



CP4 - weathered pillar cap

Pillar caps, and copings

Product	Reference	Colour	Size (cm)	Weight (kg)	Price
COPINGS - 1 m Lengths					
TWICE WEATHERED COPINGS					
Width 20cm	CH 2/20	G/P/B	99 x 20 x 4	18.5kg	
Width 25cm	CH 2/25	G/P/B	99 x 25 x 4	23.5kg	
Width 30cm	CH 2/30	G/P/B	99 x 30 x 4	29.5kg	
COPINGS - 50 cm Lengths					
TWICE WEATHERED COPINGS					
Width 18cm	CHR 2/18	G/B/P/Q	49 x 18 x 4	7.5kg	
Width 23cm	CHR 2/23	G/B/P/Q	49 x 23 x 4	10kg	
Width 28cm	CHR 2/28	G/B/P/Q	49 x 28 x 4	12kg	
Width 33cm	CHR 2/33	G/B/P/Q	49 x 33 x 4	14.5kg	
Width 45cm	CHR 2/45	G/B/P	49 x 45 x 4	22kg	
FLAT-TOPPED COPING					
Width 23cm	CHR 0/23	G/B/P	49 x 23 x 4	9kg	
Width 28cm	CHR 0/28	G/B/P	49 x 28 x 4	11kg	
Width 33cm	CHR 0/33	G/B/P	49 x 33 x 4	13.5kg	
SINGLE WEATHERED COPINGS					
Width 23cm	CHR 1/23	G/B/P	49 x 23 x 4 + 6	11.5kg	
Width 28cm	CHR 1/28	G/B/P	49 x 28 x 4 + 6	14.5kg	
Width 33cm	CHR 1/33	G/B/P	49 x 33 x 4 + 6	17.5kg	
Mortar	Weser-Mix JL		Bag	25kg	

Product	Reference	Colour	Size (cm)	Weight (kg)	Price
WEATHERED PILLAR CAP					
<i>(four times)</i>					
For 25x25cm pillars	CP 4/32	G/B/P	32 x 32 x 4	10kg	
For 30x30cm pillars	CP 4/40	G/B/P/Q	40 x 40 x 4	15kg	
For 40x40 cm pillars	CP 4/50	G/B/P/Q	50 x 50 x 5	32.5kg	
FLAT-TOPPED PILLAR CAP					
For 25x25cm pillars	CP 0/32	G/B/P	32 x 32 x 6 + 3	16kg	
For 30x30cm pillars	CP 0/40	G/B/P/Q	40 x 40 x 6 + 4	23kg	
For 40x40cm pillars	CP 0/50	G/B/P/Q	50 x 50 x 6 + 4	39kg	

G : Grey - P : Portland - B : Bathstone

Laying copings

Thoroughly clean and dampen the supporting masonry. Mix the mortar using a bonding agent, and spread it slightly proud. For long walls, we recommend placing one or two 6 or 8mm dia. steel reinforcing bars anchored in the end pillars.

When laying the copings, dampen their underside to ensure good bonding to the mortar, and press firmly into place leaving 1cm joints. Use a trowel to remove immediately any excess mortar.

It is essential to align the copings correctly using a straight-edge and a level.

Jointing

When the fixing mortar has hardened, point the copings with mortar. For Portland or Bathstone copings, we recommend using Weser-Mix JL mortar of the same colour for the joints, to avoid colour differences between the copings and the jointing. Remove any traces of mortar immediately using clean water.



UK distributor :
Addstone (UK) Limited
Tel : 01785 878 402
 www.addstone.co.uk
 sales@addstone.co.uk

WESER S.A.
 F. 37130 Mazières-de-Touraine
Tél. +33 247 962 323
Fax +33 247 964 469
 Internet : www.weser.fr

Because they are made with natural aggregates, these products may vary slightly in colour. Such differences are normal and may not be considered a cause for complaint. Weser reserves the right to alter specifications without notice.